









CE















DS-14

Intrinsically Safe Headlamp For Use In Hazardous Locations

	Low	High
Battery Size		3*AAA
Light Source	Cree XPG2 LED	
Mode	High / Low / Off	
Light Output	75lm	150lm
Beam Distance	e 75m	100m
Run Time	4hrs 30mins	2hrs 30mins
IP Rating	IP67	
Weight	143g(w/o battery)	
Dimension	80*50*45mm	

- UL	CLASS I DIV I GRP ABCD
	CLASS II DIV I GRP EFG
	CLASS III / TEMPERATURE
	CODE T4 IP67
	FILE NUMBER: E324236
- ATEX	II 1G Ex ia IIC T4 Ga IP67
	DEMINO 44 ATEN 405 IN

- ATEX	II 1G Ex ia IIC T4 Ga IP67 DEMKO 14 ATEX 1354X	
- IECEx	Ex ia IIC T4 Ga IP67 IECEx UL 14.0059X	
- CE	Approved -	

Approved

- ROHS

- DURABLE, IMPACT-RESISTANT CONSTRUCTION HEADLAMP-WITH ADJUSTABLE HEADBAND TO FIT USERS' HEAD OR HELMET
- . WITH ROTATABLE HEAD (ANGLE ADJUSTABLE BY MAXIMUM 90 DEGREE) TO MEET CUSTOMER'S VISION NEED
- . LOCKING MECHANISM ON BATTERY COMPARTMENT TO ENSURE OPEN EASILY AND SAFELY
- . AVAILABLE FOR TWO LED COLORS: WHITE: PROVIDE CLEAR AND BRIGHT LIGHT AMBER: SUITABLE FOR DARK FOG OR THICK SMOKE AREAS